

GEDORE

TOOLS FOR LIFE

Bit Socket

for Oil Drain Plug, VW-Audi



KL-0288-30



0288-30e150508_g.docx

GEDORE Automotive GmbH

Breslauer Straße 41
78166 Donaueschingen

Postfach 1329
78154 Donaueschingen - GERMANY

Phone: +49 (0) 771 / 8 32 23-0
Fax: +49 (0) 771 / 8 32 23-90

Email: info@gedore-automotive.com
Internet: www.gedore-automotive.com

KL-0288-30

VW-Audi



Size (waf)
10 mm

KL-0288-30 - Bit Socket

for Oil Drain Plug, VW-Audi

Suitable for the VW-Audi 1.2, 1.4, 1.8 and 2.0 TFSi, as well as for the 1.6 and 2.0 TDI engines equipped with a plastic oil drain plug (M14x1.5x22 mm) with special profile.

Engines installed, for example, in Audi A1, A3, A4, A5, Q5 and VW Golf VII etc.

Field of Application

Designed for the professional loosening/tightening of plastic oil drain plugs with special profile as found on oil sumps made of plastic. Necessary, for example, when changing the oil etc.


Scope of Delivery

| Part No. | Description | Qty |
|------------|--|-----|
| KL-0288-30 | Bit Socket for Oil Drain Plug, VW-Audi | 1 |

Example of Use:



Plastic oil drain plug
with special profile



Technical Data

Size (drive): 10 mm (waf)

Overall length: 35 mm



Warnings and Notes

- DO NOT operate the tool by means of an impact wrench.
- Before putting the tool into operation, visually check to ensure that it is not damaged.
- Always refer to the vehicle manufacturer's data and instructions as only these apply to all work that is carried out on the vehicle.