


# GEDORE

TOOLS FOR LIFE

## Locking Tool Set, BMW



**KL-0580-44 KA**



0580-44KAe151007.docx

### GEDORE Automotive GmbH

Breslauer Straße 41  
78166 Donaueschingen

Postfach 1329  
78154 Donaueschingen - GERMANY

Phone: +49 (0) 771 / 8 32 23-0  
Fax: +49 (0) 771 / 8 32 23-90

Email: [info@gedore-automotive.com](mailto:info@gedore-automotive.com)  
Internet: [www.gedore-automotive.com](http://www.gedore-automotive.com)

KL-0580-44 KA



BMW

### KL-0580-44 KA - Locking Tool Set, BMW

Applicable to BMW 1.6 (N40 / N45) TwinCam petrol engines.  
Fitted to BMW 1 Series (E81/E87) and 3 Series (E46/E90).  
(Engine codes: N40 B16A, N45 B16A, N45T B16AC)

#### Field of Application

Tool set for the locking/positioning of camshafts and crankshaft, as well as for pre-tensioning the timing chain tensioner. The kit also includes a tool to adjust the VANOS adjustment units. An indispensable tool set when replacing a timing chain, removing and installing VANOS adjustment units or performing an engine repair.

*For accessories, please see KL-0580-813 KB*

#### Scope of Delivery: KL-0580-44 KA

Part No./Description	Qty	Image	Cross Reference OEM Tool No.
<b>KL-0580-443 A</b> <b>Setting Gauge (Vanos)</b> For locking/adjusting the VANOS adjustment units.	1		11 7 260 <sup>*A</sup>
<b>KL-0580-442 A</b> <b>Locking Tool for Exhaust Camshaft</b> For locking the exhaust camshaft.	1		11 7 251 <sup>*A</sup>
<b>KL-0580-441 A</b> <b>Locking Tool for Inlet Camshaft</b> For locking the inlet camshaft.	1		11 7 252 <sup>*A</sup>
<b>KL-0580-8115-3 A</b> <b>Knurled Screw for Locking Tools</b> For securing the locking tools. (KL-0580-441 A + KL-0580-442 A)	1		11 7 253 <sup>*A</sup>
<b>KL-0580-8111 A</b> <b>Retaining Pin for Flywheel</b> For locking the flywheel.	1		11 9 190 <sup>*A</sup> 11 5 120 <sup>*A</sup>
<b>KL-0580-8113 A</b> <b>Pre-Tensioning Tool for Timing Chain</b> For pre-tensioning the timing chain.	1		11 9 340 <sup>*A</sup>
<b>KL-0580-4490 A - Plastic Storage Case</b>	1	<b>Warnings and Notes</b>	
		<ul style="list-style-type: none"> <li>Do not attempt to start the engine whilst tools of the <b>KL-0580-44 KA</b> locking tool set are still mounted.</li> <li>All vehicle-specific data stated herein are supplied under reserve and without commitment.</li> <li>Any work on vehicles should only be performed by qualified specialist personnel observing and complying with the directions, provisions, and safety regulations specified by the vehicle manufacturer.</li> <li>Always refer to the vehicle manufacturer's data and instructions as only these apply to all work that is carried out on the vehicle.</li> </ul>	

<sup>\*A</sup> Alternative Tool